NSN 3020-00-247-9001

Helical Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-247-9001

| Body Style: |
|--|
| Webbed, solid |
| Pitch Diameter: |
| 7.4000 inches |
| Teeth Quantity: |
| 37 |
| Bore Style: |
| W/ keyway both ends |
| Hardness Rating: |
| 91.0 rockwell c |
| Outside Diameter: |
| 7.6835 inches |
| Teeth Type: |
| Single helix |
| Tooth Form: |
| Standard |
| Tooth Direction: |
| Right |
| Pressure Angle: |
| 20.0000 degrees |
| Helix Angle: |
| 14.9167 degrees |
| Distance Between Body Face And Recessed Hub End: |
| 0.250 inches first end |
| Face Width: |
| 3.000 inches |
| Bore Diameter: |
| 3.125 inches first end |
| Keyway Width: |
| 0.749 inches first end |
| Distance From Bore Center To Keyway Bottom: |
| 1.7739 inches first end |
| Hub Style Designator: |
| Plain both ends |
| Hub Diameter: |
| 4.500 inches second end |
| Material: |
| Steel |
| Material Specification: |
| Mil-s-890, class c military specification single material response |
| Style Designator: |

Recessed hubs

NSN 3020-00-247-9001

Helical Gear - Page 2 of 2



| N/a | |
|-------------------|--|
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| | |
| No | |
| No Fiig: | |

Mil-std (military Standard):

Mil-s-890 spec.

Shelf Life: