## NSN 3020-00-249-5415

Spur Gear - Page 1 of 2

**Body Style:** 



View Online at https://aerobasegroup.com/nsn/3020-00-249-5415

Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
Between 2.6990 inches and 2.7000 inches
Teeth Quantity:
216
Bore Style:
Plain both ends
Mounting Hole Thread Series Designator:
Unf axially through body, first end
Mounting Hole Thready Qty Per Inch (tpi):
80 axially through body, first end
Mounting Hole Thread Size:
0.060 inches axially through body, first end
Mounting Hole Type And Quantity:
4 threaded axially through body, first end
Outside Diameter:
2.723 inches
Nominallength:
0.156 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.031 inches both ends
Face Width:
0.094 inches
Bore Diameter:
2.280 inches both ends
2.280 inches both ends  Hub Style Designator:
Hub Style Designator:
Hub Style Designator: Plain both ends
Hub Style Designator: Plain both ends Hub Diameter:
Hub Style Designator: Plain both ends Hub Diameter: 2.644 inches both ends
Hub Style Designator: Plain both ends Hub Diameter: 2.644 inches both ends Bolt Hole Circle Diameter:
Hub Style Designator: Plain both ends Hub Diameter: 2.644 inches both ends Bolt Hole Circle Diameter: 2.432 inches axially through body, first end
Hub Style Designator: Plain both ends Hub Diameter: 2.644 inches both ends Bolt Hole Circle Diameter: 2.432 inches axially through body, first end Material:
Hub Style Designator: Plain both ends Hub Diameter: 2.644 inches both ends Bolt Hole Circle Diameter: 2.432 inches axially through body, first end Material: Aluminum alloy 6061

## NSN 3020-00-249-5415

Spur Gear - Page 2 of 2



_	•		_			
<b>ن</b>	ırfa	$\sim$	Irο	o+n	20r	٠.
u	ai ia	uc.	116	аш	161	IL.

Anodize

**Style Designator:** 

Protruding hubs

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A27300