## NSN 3020-00-251-4923

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-251-4923

Body Style:
Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
Between 3.7350 inches and 3.7500 inches
Teeth Quantity:
90
Bore Style:
Plain both ends
Mounting Hole Type And Quantity:
4 counterbored axially through body, second end
Outside Diameter:
3.832 inches
Tooth Form:
Standard
Pressure Angle:
14.5000 degrees
Distance Between Body Face And Protruding Hub End:
0.190 inches first end
Face Width:
0.120 inches
Bore Diameter:
1.000 inches both ends
Hub Style Designator:
1 step first end
End Length:
0.088 inches first end
Precision Classification:
Quality number 12
End Diameter:
1.7713 inches first end
First Step Length:
0.105 inches first end
First Step Diameter:
2.000 inches first end
Mounting Hole Diameter:
0.1440 inches axially through body, second end
Bolt Hole Circle Diameter:

Material:

Aluminum alloy

1.3740 inches axially through body, second end

## NSN 3020-00-251-4923

Spur Gear - Page 2 of 2



Material	Specification:
----------	----------------

Qq-a-250/4 federal specification single material response

**Style Designator:** 

Protruding hub

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A27300