

View Online at <https://aerobasegroup.com/nsn/3020-00-251-7981>

**Groove Depth:**

0.6925 inches

**Groove Width:**

0.678 inches

**Outside Diameter:**

Between 5.716 inches and 5.732 inches

**Overall Length:**

3.813 inches

**Bolt Circle Diameter:**

2.250 inches

**Bore Diameter:**

Between 1.2505 inches and 1.2515 inches

**Bore Length:**

0.750 inches

**Drilled Hole Diameter:**

0.34375 inches

**V Groove Angle In Deg:**

36.0

**Pitch Diameter:**

5.094 inches

**Securing Hole Quantity:**

4

**Material And Location:**

Iron, g-13m, general motors corporation

**Face Width:**

1.750 inches

**Design Form:**

Webbed

**Bore Type:**

Straight

**Bearings:**

Not included

**Groove Quantity:**

2

**Counterbore Feature:**

Not included

**Hole Location:**

On hub

**Keying Facility:**

Not included

**Securing Method:**

Drilled hole

**Split Hub Feature:**

Not included

**Web/spoke Relationship To Face Centerline:**

Offset

**Lightening Hole:**

Not included

**Integral Cooling Vane:**

Not included

**Groove Shape:**

V

**Bore Feature:**

Included

**Protruding Hub Characteristic:**

Stepped

**Securing Location:**

Aa end

**Hub End Outside Diameter And Location:**

3.125 inches both ends

**Distance From Outside Flange/rim To Hub End And Location:**

2.063 inches both ends

**First Step Face Largest Diameter And Location:**

4.156 inches both ends

**First Step Length And Location:**

0.813 inches both ends

**Style Designator:**

Webbed or spoked

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T353-a