

View Online at <https://aerobasegroup.com/nsn/3020-00-252-7359>

End Application:

Austin ship class lpd-4 amphibious transport docks. Fleet vertical package conveyers. Tarawa class lha, emory s. Land class as, forrestal class cv, nimitz class lhd, wasp class lhd, supply class aoe, shipboard material handling equipment (mhe). Utili type 115 ft landing craft.

Pitch Distance:

1.250 inches

Link Row Quantity:

1

First Chain Link Style:

Roller

Second Chain Link Style:

Pin

Pin Fastening Method:

Cotter pin

First Chain Link Plate Width:

1.188 inches

First Chain Link Plate Thickness:

0.1560 inches

First Chain Link Roller Diameter:

0.7500 inches

First Chain Link Width Between Plates:

0.7500 inches

Second Chain Link Plate Width:

1.0250 inches

Second Chain Link Plate Thickness:

0.1560 inches

Second Chain Link Pin Diameter:

0.3750 inches

Second Chain Link Width Between Plates:

1.0620 inches

Min. Tensile Strength (psi):

9500 pounds per square inch

Criticality Code Justification:

Feat

Special Features:

Weapon system essential

Material:

Steel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A23500