## NSN 3020-00-255-1498

Spur Gear Sector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-255-1498

Tooth Oversity
Teeth Quantity:
32
Bore Style:
Plain both ends
Pitch Radius:
1.0000 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.250 inches first end
Face Width:
0.125 inches
Bore Diameter:
0.250 inches both ends
Hub Style Designator:
Pinned first end
Hub Diameter:
0.500 inches first end
Outside Radius:
1.016 inches
Precision Classification:
Quality number 10
Arc Length:
1.082 inches
Special Features:
One headed grooved pin mounted on gear face between teeth and hub with a press fit securing method
Material:
Steel comp 303
Material Specification:
Qq-s-764, cond a federal specification single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Mil-f-14072, finish f300 military specification single treatment response
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:

## NSN 3020-00-255-1498

Spur Gear Sector - Page 2 of 2



Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-f-14072 spec.