NSN 3020-00-255-9950

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-255-9950

Outside Diameter:
3.720 inches
Overall Length:
2.375 inches
Keyway Width:
0.250 inches
Bore Diameter:
Between 1.1498 inches and 1.250 inches
Bore Length:
2.375 inches
Distance From Center Of Bore To Bottom Of Keyway:
0.737 inches
Pitch Diameter:
3.401 inches
Face Width:
Between 1.740 inches and 1.752 inches
Guide:
Not included
Design Form:
Plain
Bore Type:
Bore Type: Straight
Straight
Straight Metallic Hardness Rating And Location:
Straight Metallic Hardness Rating And Location: 50.0 rockwell c hub and 55.0 rockwell c hub
Straight Metallic Hardness Rating And Location: 50.0 rockwell c hub and 55.0 rockwell c hub Counterbore Feature:
Straight Metallic Hardness Rating And Location: 50.0 rockwell c hub and 55.0 rockwell c hub Counterbore Feature: Not included
Straight Metallic Hardness Rating And Location: 50.0 rockwell c hub and 55.0 rockwell c hub Counterbore Feature: Not included Keying Facility:
Straight Metallic Hardness Rating And Location: 50.0 rockwell c hub and 55.0 rockwell c hub Counterbore Feature: Not included Keying Facility: Included
Straight Metallic Hardness Rating And Location: 50.0 rockwell c hub and 55.0 rockwell c hub Counterbore Feature: Not included Keying Facility: Included Keying Facility Type:
Straight Metallic Hardness Rating And Location: 50.0 rockwell c hub and 55.0 rockwell c hub Counterbore Feature: Not included Keying Facility: Included Keying Facility Type: Keyway
Straight Metallic Hardness Rating And Location: 50.0 rockwell c hub and 55.0 rockwell c hub Counterbore Feature: Not included Keying Facility: Included Keying Facility Type: Keyway Lightening Hole: Not included
Straight Metallic Hardness Rating And Location: 50.0 rockwell c hub and 55.0 rockwell c hub Counterbore Feature: Not included Keying Facility: Included Keying Facility Type: Keyway Lightening Hole:
Straight Metallic Hardness Rating And Location: 50.0 rockwell c hub and 55.0 rockwell c hub Counterbore Feature: Not included Keying Facility: Included Keying Facility Type: Keyway Lightening Hole: Not included Protruding Hub Characteristic: Plain
Straight Metallic Hardness Rating And Location: 50.0 rockwell c hub and 55.0 rockwell c hub Counterbore Feature: Not included Keying Facility: Included Keying Facility Type: Keyway Lightening Hole: Not included Protruding Hub Characteristic:
Straight Metallic Hardness Rating And Location: 50.0 rockwell c hub and 55.0 rockwell c hub Counterbore Feature: Not included Keying Facility: Included Keying Facility Type: Keyway Lightening Hole: Not included Protruding Hub Characteristic: Plain Belt/chain/film Size For Which Designed:
Straight Metallic Hardness Rating And Location: 50.0 rockwell c hub and 55.0 rockwell c hub Counterbore Feature: Not included Keying Facility: Included Keying Facility Type: Keyway Lightening Hole: Not included Protruding Hub Characteristic: Plain Belt/chain/film Size For Which Designed: Roller Chain Pitch Type For Which Designed:
Straight Metallic Hardness Rating And Location: 50.0 rockwell c hub and 55.0 rockwell c hub Counterbore Feature: Not included Keying Facility: Included Keying Facility Type: Keyway Lightening Hole: Not included Protruding Hub Characteristic: Plain Belt/chain/film Size For Which Designed: Roller Chain Pitch Type For Which Designed: Single pitch
Straight Metallic Hardness Rating And Location: 50.0 rockwell c hub and 55.0 rockwell c hub Counterbore Feature: Not included Keying Facility: Included Keying Facility Type: Keyway Lightening Hole: Not included Protruding Hub Characteristic: Plain Belt/chain/film Size For Which Designed: Roller Chain Pitch Type For Which Designed:

0.707 inches

NSN 3020-00-255-9950 Sprocket Wheel - Page 2 of 2



Teeth Quantity Per Row:
17
Asa Standard Chain Number:
50-3
Hardness Rating Test Method:
Rockwell
Teeth Hardness Rating:
Between 50.0 rockwell c and 55.0 rockwell c
Bore Bearing:
Not included
Hub External Keyway:
Not included
Tooth Pitch:
0.625 inches
Hub End Outside Diameter And Location:
2.500 inches both ends
Distance From Outside Flange/rim To Hub End And Location:
0.3145 inches both ends
Material:
Steel, sae 1040 or steel, sae 1045
Material:
Steel comp 1040 or steel comp 1045
Material Specification:
Sae 1040 assn standard 1st material response and sae 1045 assn standard 2nd material response
Quantity:
1
Style Designator:
Plain
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T353-c