

View Online at <https://aerobasegroup.com/nsn/3020-00-256-4189>

Groove Depth:

0.688 inches

Groove Width:

Between 0.654 inches and 0.658 inches

Outside Diameter:

4.813 inches

Overall Length:

1.750 inches

Keyway Width:

Between 0.157 inches and 0.159 inches

Thread Size:

3/8 - 16

Bore Diameter:

Between 0.624 inches and 0.625 inches

Bore Length:

1.500 inches

Distance From Center Of Bore To Bottom Of Keyway:

Between 0.3875 inches and 0.3905 inches

V Groove Angle In Deg:

38.0

Securing Hole Quantity:

1

Material And Location:

Iron, 102, superior engine co

Face Width:

0.875 inches

Design Form:

Webbed

Bore Type:

Straight

Bearings:

Not included

Groove Quantity:

1

Counterbore Feature:

Not included

Hole Location:

Located 180 degrees from keyway

Keying Facility:

Included

Keying Facility Type:

Keyway

Securing Method:

Threaded hole

Split Hub Feature:

Not included

Web/spoke Relationship To Face Centerline:

Offset

Lightening Hole:

Not included

Integral Cooling Vane:

Not included

Groove Shape:

V

Standard V-belt Section Designation For Which Designed:

B

Bore Feature:

Included

Securing Location:

Aa end

Hub End Outside Diameter And Location:

1.500 inches both ends

Distance From Outside Flange/rim To Hub End And Location:

0.875 inches aa end and 0.250 inches bb end

Special Features:

Rim beveled 45 deg, 1/8 in. Deep, 3-1/8 in. Dia

Quantity:

1

Style Designator:

Webbed or spoked

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T353-a