NSN 3020-00-258-1714

Sprocket Wheel - Page 1 of 2

Counterbore Diameter:

Counterbore Depth:

Outside Diameter:

1.082 inches

0.188 inches

5.710 inches **Overall Length:**



View Online at https://aerobasegroup.com/nsn/3020-00-258-1714

0.938 inches
Keyway Width:
0.188 inches
Bore Diameter:
1.062 inches
Bore Length:
0.719 inches
Distance From Center Of Bore To Bottom Of Keyway
0.625 inches
Pitch Diameter:
5.495 inches
Face Width:
0.561 inches
Design Form:
Spoked
Bore Type:
Straight
Counterbore Feature:
Included
Counterbore Location:
Aa end
Keying Facility:
Included
Keying Facility Type:
Keyway
Lightening Hole:
Not included
Protruding Hub Characteristic:
Plain
Belt/chain/film Size For Which Designed:
Roller chain
Roller Chain Pitch Type For Which Designed:
Single pitch
Teeth Row Quantity:
2

NSN 3020-00-258-1714 Sprocket Wheel - Page 2 of 2



Center To Center Distance Between Teeth Rows:	
0.399 inches	
Teeth Quantity Per Row:	
46	
Asa Standard Chain Number:	
35-2	
Hardness Rating Test Method:	
Not rated	
Bore Bearing:	
Not included	
Hub External Keyway:	
Not included	
Tooth Pitch:	
0.375 inches	
Hub End Outside Diameter And Location:	
1.750 inches both ends	
Distance From Outside Flange/rim To Hub End And Location:	
0.375 inches aa end and 0.219 inches bb end	
Material:	
Iron, cast	
Material:	
Iron cast	
Quantity:	
1	
Style Designator:	
Webbed or spoked	
Shelf Life:	
N/a	
Unit Of Measure:	
-	
Demilitarization:	
No	
Fiig:	
Т353-с	