## NSN 3020-00-262-7941

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-262-7941

Body Style:
Plain, solid
Pitch Diameter:
Between 0.5198 inches and 0.5208 inches
Teeth Quantity:
25
Bore Style:
Plain both ends
Backlash Designation:
Grade c
Outside Diameter:
0.562 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.250 inches first end
Face Width:
0.125 inches
Bore Diameter:
0.250 inches both ends
Hub Style Designator:
Plain first end
Hub Diameter:
0.406 inches first end
Precision Classification:
Quality number 10
Special Features:
1 0.055 in. Diameter plain hole and 1 0.138 in. Diameter threaded hole 90.0 degrees apart on hub for positioning
Material:
Steel comp 303
Material Specification:
Qq-s-764, type 303, cond a federal specification single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Mil-f-14072, finish e300 military specification single treatment response
Style Designator:
Protruding hub
Shelf Life:
N/a

## NSN 3020-00-262-7941

Spur Gear - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-f-14072 spec.