
# NSN 3020-00-264-8559

Spur Gear - Page 1 of 2



#### **Body Style:**

Plain, solid

#### **Attachment Method:**

Clamp

### **Pitch Diameter:**

Between 0.6657 inches and 0.6667 inches

### **Teeth Quantity:**

64

Bore Style:

Plain both ends

- **Outside Diameter:**
- 0.687 inches

#### Tooth Form:

Standard

#### Pressure Angle:

20.0000 degrees

#### Distance Between Body Face And Protruding Hub End:

0.281 inches first end

#### Face Width:

0.125 inches

### Bore Diameter:

0.125 inches both ends

### Hub Style Designator:

Split first end

### Hub Diameter:

0.188 inches first end

#### **Clamping Surface Length:**

0.250 inches first end

#### End Length:

0.250 inches first end

#### **Precision Classification:**

Quality number 10

#### **Special Features:**

Hub is also stepoped, 0.250 in dia, 0.031 in.Lg

#### Material:

Steel comp 303

### Material Specification:

Qq-s-764, type 303, cond a federal specification single material response

#### Surface Treatment:

Passivate

#### Surface Treatment Specification:

Qq-p-35, type 1 federal specification single treatment response



# NSN 3020-00-264-8559

Spur Gear - Page 2 of 2



**AeroBase** 

Style Designator:

Protruding hub

## **Reference Number Differentiating Characteristics:**

As differentiated by special features

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300