NSN 3020-00-266-7669

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-266-7669

Outside Diameter:
Between 3.442 inches and 3.472 inches
Overall Length:
0.938 inches
Keyway Width:
0.253 inches
Key Width:
Between 0.251 inches and 0.253 inches
Bore Diameter:
Between 1.500 inches and 1.505 inches
Bore Length:
0.938 inches
Distance From Center Of Bore To Bottom Of Keyway:
Between 0.870 inches and 0.875 inches
Pitch Diameter:
3.196 inches
Face Width:
0.284 inches
Design Form:
Plain
Bore Type:
Straight
Metallic Hardness Rating And Location:
35.0 rockwell c hub and 45.0 rockwell c hub
Counterbore Feature:
Not included
Keying Facility:
Included
Keying Facility Type:
Keyway
Lightening Hole:
Not included
Belt/chain/film Size For Which Designed:
Roller chain
Roller Chain Pitch Type For Which Designed:
Single pitch
Teeth Row Quantity:
1
Teeth Quantity Per Row:
20
Asa Standard Chain Number:

40

NSN 3020-00-266-7669 Sprocket Wheel - Page 2 of 2



Hardness Rating Test Method:
Rockwell
Teeth Hardness Rating:
Between 35.0 rockwell c and 45.0 rockwell c
Bore Bearing:
Not included
Tooth Pitch:
0.500 inches
Hub End Outside Diameter And Location:
2.625 inches both ends
Distance From Outside Flange/rim To Hub End And Location:
0.452 inches aa end and 0.201 inches bb end
Special Features:
0.062 in. Deep by 45 degrees angle chamfer on bore end on 1st end of hub, 0.125 in. Diameter hole drilled on a 8 degrees angle frombase
of teeth @into bore on 2nd end of hub
Material:
Steel, sae 1020
Material:
Steel comp 1020
Material Specification:
Sae 1020 assn standard single material response
Quantity:
1
Style Designator:
Plain
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T353-c