NSN 3020-00-270-3540

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-270-3540

Spline Major Diameter:
Between 0.874 inches and 0.875 inches
Outside Diameter:
Between 5.710 inches and 5.720 inches
Overall Length:
Between 2.115 inches and 2.135 inches
Spline Quantity:
6
Spline Minor Diameter:
Between 0.743 inches and 0.744 inches
Pitch Diameter:
5.324 inches
Face Width:
Between 0.424 inches and 0.436 inches
Design Form:
Webbed
Bore Type:
Straight spline
Spline Length:
Between 2.115 inches and 2.135 inches
Counterbore Feature:
Not included
Keying Facility:
Not included
Lightening Hole:
Not included
Protruding Hub Characteristic:
Stepped
Groove/step Location:
Both ends
Belt/chain/film Size For Which Designed:
Roller chain
Roller Chain Pitch Type For Which Designed:
Single pitch
Teeth Row Quantity:
1
Teeth Quantity Per Row:
11
Hardness Rating Test Method:
Not rated
Bore Bearing:

Not included

NSN 3020-00-270-3540 Sprocket Wheel - Page 2 of 2



Hub External Keyway:
Not included
Tooth Pitch:
1.500 inches
Hub End Outside Diameter And Location:
1.500 inches both ends
Distance From Outside Flange/rim To Hub End And Location:
0.847 inches both ends and 0.848 inches both ends
First Step Face Largest Diameter And Location:
1.865 inches both ends and 1.885 inches both ends
Second Step Face Largest Diameter And Location:
4.000 inches both ends and 4.020 inches both ends
First Step Length And Location:
0.563 inches both ends
Second Step Length And Location:
0.235 inches both ends
Material:
Steel, mil-s-890, class b
Material:
Steel
Material Specification:
Mil-s-890, class b military specification single material response
Style Designator:
Webbed or spoked
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
Т353-с
Mil-std (military Standard):
Mil-s-890 spec.