## NSN 3020-00-271-9988

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-271-9988

Body Style:
Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
2.4810 inches
Teeth Quantity:
40
Bore Style:
W/ 2 keyways both ends
Mounting Hole Thread Series Designator:
Unc transversely through hub, first end
Mounting Hole Thread Size:
0.250 inches axially through body, first end
Mounting Hole Type And Quantity:
1 threaded transversely through hub, first end
Outside Diameter:
2.606 inches
Nominallength:
1.062 inches
Tooth Form:
Standard
Pressure Angle:
14.5000 degrees
Distance Between Body Face And Protruding Hub End:
0.218 inches first end
Face Width:
0.844 inches
Bore Diameter:
0.656 inches both ends
Keyway Width:
0.187 inches both ends
Distance From Bore Center To Keyway Bottom:
0.422 inches both ends
Hub Style Designator:
Pinned first end
Hub Diameter:
1.125 inches first end
Mounting Hole Diameter:
0.086 inches transversely through hub, first end

**Bolt Hole Circle Diameter:** 

1.750 inches transversely through hub, first end

## NSN 3020-00-271-9988

Spur Gear - Page 2 of 2

Material:



Steel
Material Specification:
Mil-s-890, alloy no 2 military specification single material response
Surface Treatment:
Phosphate manganese
Surface Treatment Specification:
Mil-c-16232 military specification single treatment response
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300
Mil-std (military Standard):
Mil-s-890 spec.