NSN 3020-00-275-0913

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-275-0913

Counterbore Diameter: Between 2.046 inches and 2.047 inches and 2.046 inches and 2.047 inches **Counterbore Depth:** Between 0.405 inches and 0.408 inches and 0.372 inches **Outside Diameter:** Between 5.710 inches and 5.720 inches **Overall Length:** Between 1.570 inches and 1.580 inches **Bore Diameter:** Between 1.740 inches and 1.760 inches Bore Length: Between 1.570 inches and 1.580 inches **Pitch Diameter:** 5.324 inches Face Width: Between 0.424 inches and 0.436 inches **Design Form:** Webbed Bore Type: Straight **Counterbore Feature:** Included **Counterbore Location:** Both ends **Keying Facility:** Not included **Lightening Hole:** Not included Belt/chain/film Size For Which Designed: Roller chain **Roller Chain Pitch Type For Which Designed:** Single pitch **Teeth Row Quantity:** 1 **Teeth Quantity Per Row:** 11 Hardness Rating Test Method: Not rated **Bore Bearing:** Not included **Tooth Pitch:**

1.500 inches

NSN 3020-00-275-0913

Sprocket Wheel - Page 2 of 2



Hub End Outside Diameter And Location:

2.590 inches both ends and 2.610 inches both ends

Distance From Outside Flange/rim To Hub End And Location:

0.575 inches both ends

Material:

Steel, mil-s-890

Material:

Steel

Material Specification:

Mil-s-890 military specification single material response

Style Designator:

Webbed or spoked

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

T353-c

Mil-std (military Standard):

Mil-s-890 spec.