## NSN 3020-00-277-1101

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-277-1101

Outside Diameter:
Between 4.013 inches and 4.033 inches
Overall Length:
Between 3.997 inches and 4.000 inches
Bore Diameter:
Between 2.374 inches and 2.375 inches
Bore Length:
Between 3.997 inches and 4.000 inches
Pitch Diameter:
3.826 inches
Furnished Items And Quantity:
One bushing
Face Width:
3.875 inches
Guide:
Not included
Design Form:
Plain
Bore Type:
Straight
Metallic Hardness Rating And Location:
38.0 rockwell c body and 44.0 rockwell c body
Counterbore Feature:
Not included
Keying Facility:
Not included
Lightening Hole:
Not included
Belt/chain/film Size For Which Designed:
Roller chain
Roller Chain Pitch Type For Which Designed:
Single pitch
Teeth Row Quantity:
4
Center To Center Distance Between Teeth Rows:
Between 0.395 inches and 0.405 inches
Teeth Quantity Per Row:
32
Asa Standard Chain Number:
35-4
Hardness Rating Test Method:

Rockwell

## **NSN 3020-00-277-1101** Sprocket Wheel - Page 2 of 2



Teeth Hardness Rating:	
38.0 rockwell c	
Bore Bearing:	
Not included	
Hub External Keyway:	
Not included	
Tooth Pitch:	
0.375 inches	
Special Features:	
Clearance core in center of bore, @drilled and tapped for 0.125 in. Pipe tap	
Material:	
Steel, qq-s-633, fs1020-canceled	
Material:	
Steel comp 1020	
Material Specification:	
Qq-s-633, fs1020-canceled federal specification single material response	
Style Designator:	
Plain	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
T353-c	