NSN 3020-00-277-1113Spur Gear - Page 1 of 2



opul deal Tage For 2	
View Online at https://aerobasegroup.com/nsn/3020-00-277-1113	
Body Style:	
Webbed, with lightening holes	
Attachment Method:	
Mounting hole	
Pitch Diameter:	
8.6000 inches	
Teeth Quantity:	
43	
Bore Style:	
W/ keyway both ends	
Mounting Hole Thread Series Designator:	
Unc axially through body, first end	
Mounting Hole Thread Size:	
0.375 inches axially through body, first end	
Mounting Hole Type And Quantity:	
2 threaded axially through body, first end	
Outside Diameter:	
9.000 inches	
Tooth Form:	
Standard	
Pressure Angle:	
20.0000 degrees	
Face Width:	
1.750 inches	
Bore Diameter:	
2.377 inches both ends	
Keyway Width:	
0.625 inches both ends	
Distance From Bore Center To Keyway Bottom:	
1.5005 inches both ends	
Hub Style Designator:	
Plain both ends	
Hub Diameter:	
3.9375 inches both ends	
Bolt Hole Circle Diameter:	
3.188 inches axially through body, first end	
Material:	
Copper alloy	
Material Specification:	

Mil-b-16522 class 1 bronze manganese military specification single material response

Style Designator:

Flush hub

NSN 3020-00-277-1113

Spur Gear - Page 2 of 2



Sneir	Lite:
N/a	

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-b-16522 spec.