

View Online at <https://aerobasegroup.com/nsn/3020-00-277-3787>

Groove Depth:

0.688 inches

Groove Width:

Between 0.677 inches and 0.679 inches

Outside Diameter:

5.900 inches

Overall Length:

3.500 inches

Keyway Width:

0.250 inches

Thread Size:

3/8 - 16

Bore Diameter:

Between 1.125 inches and 1.128 inches

Bore Length:

2.875 inches

Distance From Center Of Bore To Bottom Of Keyway:

0.688 inches

V Groove Angle In Deg:

38.0

Pitch Diameter:

5.400 inches

Securing Hole Quantity:

2

Material And Location:

Aluminum alloy, mil-a-17129, class 3-canceled

Face Width:

2.500 inches

Design Form:

Webbed

Bore Type:

Straight

Bearings:

Not included

Groove Quantity:

3

Counterbore Feature:

Not included

Hole Location:

One hole located on top of keyway, one hole located 90 degrees from keyway, both holes located 5/8 in. From end of hub

Keying Facility:

Included

Keying Facility Type:

Keyway

Securing Method:

Threaded hole

Split Hub Feature:

Not included

Web/spoke Relationship To Face Centerline:

Offset

Lightening Hole:

Not included

Integral Cooling Vane:

Not included

Groove Shape:

V

Standard V-belt Section Designation For Which Designed:

B

Bore Feature:

Included

Securing Location:

Aa end

Hub End Outside Diameter And Location:

2.500 inches both ends

Distance From Outside Flange/rim To Hub End And Location:

1.000 inches both ends

Quantity:

1

Style Designator:

Webbed or spoked

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T353-a