NSN 3020-00-278-5152

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-278-5152

Attachment Method:
Mounting hole
Pitch Diameter:
0.8125 inches
Teeth Quantity:
52
Bore Style:
Plain both ends
Mounting Hole Type And Quantity:
3 countersunk axially through body, second end
Outside Diameter:
0.843 inches
Tooth Form:
Stub
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.020 inches first end
Face Width:
0.119 inches
Bore Diameter:
0.2194 inches both ends
Hub Style Designator:
Plain first end
Hub Diameter:
0.750 inches first end
Precision Classification:
Quality number 9
Mounting Hole Diameter:
0.070 inches axially through body, second end
Bolt Hole Circle Diameter:
0.172 inches axially through body, second end
Material:
Steel comp 303 or steel comp 303s hub
Material Specification:
Qq-a-225/6, t4 federal specification single material response body
Surface Treatment:
Passivate hub
Surface Treatment Specification:
Mil-f-14072, finish 300 military specification single treatment response hub
Style Designator:
Protruding hub

NSN 3020-00-278-5152

Spur Antibacklash Gear - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-s-7720 spec.

