## NSN 3020-00-278-7602

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-278-7602 **Outside Diameter:** 3.438 inches **Overall Length:** 0.938 inches **Key Width:** 0.250 inches **Bore Diameter:** 1.500 inches **Bore Length:** 0.938 inches Distance From Center Of Bore To Bottom Of Keyway: 0.875 inches **Drilled Hole Diameter:** 0.125 inches Pitch Diameter: 3.196 inches **Securing Hole Quantity:** Face Width: 0.281 inches Guide: Not included **Design Form:** Plain **Bore Type:** Straight **Metallic Hardness Rating And Location:** 35.0 rockwell c hub and 45.0 rockwell c hub **Counterbore Feature:** Not included **Hole Location:** 180 degrees from keyway **Keying Facility:** Included **Keying Facility Type:** Keyway **Securing Method:** Drilled hole **Lightening Hole:** Not included

**Protruding Hub Characteristic:** 

Plain

## NSN 3020-00-278-7602

Sprocket Wheel - Page 2 of 2



Conving Location.
Securing Location:
Aa end
Belt/chain/film Size For Which Designed:
Roller chain
Roller Chain Pitch Type For Which Designed:
Single pitch
Teeth Row Quantity:
1
Teeth Quantity Per Row:
20
Asa Standard Chain Number:
40
Hardness Rating Test Method:
Rockwell
Teeth Hardness Rating:
Between 35.0 rockwell c and 45.0 rockwell c
Bore Bearing:
Not included
Hub External Keyway:
Not included
Tooth Pitch:
0.500 inches
Hub End Outside Diameter And Location:
2.625 inches both ends
Distance From Outside Flange/rim To Hub End And Location:
0.438 inches aa end and 0.219 inches bb end
Material:
Steel, qq-s-633, fsb1113-canceled
Material:
Steel comp 1213
Material Specification:
Qq-s-633, fsb1113-canceled federal specification single material response
Quantity:
1
Style Designator:
Plain
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:

Т353-с