## NSN 3020-00-281-3367



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-281-3367 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: Between 0.3740 inches and 0.3750 inches **Teeth Quantity:** 24 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 56 transversely through hub, first end **Mounting Hole Thread Size:** 0.086 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 2 threaded transversely through hub, first end **Outside Diameter:** 0.405 inches Nominallength: 0.312 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.187 inches first end **Face Width:** 0.125 inches **Bore Diameter:** 0.120 inches both ends

**Hub Style Designator:** Pinned first end **Hub Diameter:** 0.297 inches first end **Precision Classification:** 

Quality number 10 or quality number 11

**Special Features:** 

Mounting holes located 180 degrees apart

Material:

Steel comp 303

## NSN 3020-00-281-3367

Spur Gear - Page 2 of 2

A27300

Mil-std (military Standard):

Mil-f-14072 spec.



Material Specification:
Qq-s-764, type 303, cond a federal specification single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Mil-f-14072, finish e300 military specification single treatment response
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: