NSN 3020-00-287-7285

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-287-7285

Body Style:
Webbed, solid
Spline Quantity:
10 both ends
Pitch Diameter:
3.0000 inches
Teeth Quantity:
30
Bore Style:
Involute spline both ends
Spline Pitch Diameter:
0.9380 inches both ends
Hardness Rating:
30.0 rockwell c and 35.0 rockwell c
Outside Diameter:
3.199 inches
Nominallength:
1.969 inches
Tooth Form:
Standard
Pressure Angle:
riessure Angle.
14.5000 degrees
14.5000 degrees
14.5000 degrees Distance Between Body Face And Protruding Hub End:
14.5000 degrees Distance Between Body Face And Protruding Hub End: 1.094 inches first end
14.5000 degrees Distance Between Body Face And Protruding Hub End: 1.094 inches first end Body Recess Depth:
14.5000 degrees Distance Between Body Face And Protruding Hub End: 1.094 inches first end Body Recess Depth: 0.594 inches second end
14.5000 degrees Distance Between Body Face And Protruding Hub End: 1.094 inches first end Body Recess Depth: 0.594 inches second end Face Width:
14.5000 degrees Distance Between Body Face And Protruding Hub End: 1.094 inches first end Body Recess Depth: 0.594 inches second end Face Width: 0.875 inches
14.5000 degrees Distance Between Body Face And Protruding Hub End: 1.094 inches first end Body Recess Depth: 0.594 inches second end Face Width: 0.875 inches Bore Diameter:
14.5000 degrees Distance Between Body Face And Protruding Hub End: 1.094 inches first end Body Recess Depth: 0.594 inches second end Face Width: 0.875 inches Bore Diameter: 1.015 inches both ends
14.5000 degrees Distance Between Body Face And Protruding Hub End: 1.094 inches first end Body Recess Depth: 0.594 inches second end Face Width: 0.875 inches Bore Diameter: 1.015 inches both ends Counterbore Depth:
14.5000 degrees Distance Between Body Face And Protruding Hub End: 1.094 inches first end Body Recess Depth: 0.594 inches second end Face Width: 0.875 inches Bore Diameter: 1.015 inches both ends Counterbore Depth: 0.594 inches second end
14.5000 degrees Distance Between Body Face And Protruding Hub End: 1.094 inches first end Body Recess Depth: 0.594 inches second end Face Width: 0.875 inches Bore Diameter: 1.015 inches both ends Counterbore Depth: 0.594 inches second end Counterbore Diameter:
14.5000 degrees Distance Between Body Face And Protruding Hub End: 1.094 inches first end Body Recess Depth: 0.594 inches second end Face Width: 0.875 inches Bore Diameter: 1.015 inches both ends Counterbore Depth: 0.594 inches second end Counterbore Diameter: 1.015 inches second end
14.5000 degrees Distance Between Body Face And Protruding Hub End: 1.094 inches first end Body Recess Depth: 0.594 inches second end Face Width: 0.875 inches Bore Diameter: 1.015 inches both ends Counterbore Depth: 0.594 inches second end Counterbore Diameter: 1.015 inches second end Hub Style Designator:
14.5000 degrees Distance Between Body Face And Protruding Hub End: 1.094 inches first end Body Recess Depth: 0.594 inches second end Face Width: 0.875 inches Bore Diameter: 1.015 inches both ends Counterbore Depth: 0.594 inches second end Counterbore Diameter: 1.015 inches second end Hub Style Designator: 1 step first end
14.5000 degrees Distance Between Body Face And Protruding Hub End: 1.094 inches first end Body Recess Depth: 0.594 inches second end Face Width: 0.875 inches Bore Diameter: 1.015 inches both ends Counterbore Depth: 0.594 inches second end Counterbore Diameter: 1.015 inches second end Hub Style Designator: 1 step first end End Length:
14.5000 degrees Distance Between Body Face And Protruding Hub End: 1.094 inches first end Body Recess Depth: 0.594 inches second end Face Width: 0.875 inches Bore Diameter: 1.015 inches both ends Counterbore Depth: 0.594 inches second end Counterbore Diameter: 1.015 inches second end Hub Style Designator: 1 step first end End Length: 0.968 inches first end

0.125 inches first end

NSN 3020-00-287-7285

Spur Gear - Page 2 of 2

A27300



First Step Diameter:
2.250 inches first end
Special Features:
Spline nom. Minor dia. 0.863 in.
Material:
Steel comp 1144
Material Specification:
66 federal standard single material response and aisi/sae 1144 assn standard single material response
Style Designator:
Protruding hub, recessed body
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: