

View Online at <https://aerobasegroup.com/nsn/3020-00-287-8681>

Spline Major Diameter:

Between 1.498 inches and 1.500 inches

Outside Diameter:

6.126 inches

Overall Length:

Between 1.437 inches and 1.563 inches

Spline Quantity:

6

Spline Minor Diameter:

Between 1.274 inches and 1.275 inches

Thread Size:

3/8-24

Pitch Diameter:

5.746 inches

Securing Hole Quantity:

1

Face Width:

Between 0.448 inches and 0.459 inches

Guide:

Not included

Design Form:

Plain

Bore Type:

Straight spline

Spline Length:

Between 1.437 inches and 1.563 inches

Counterbore Feature:

Not included

Hole Location:

Located on top of spline

Keying Facility:

Not included

Securing Method:

Threaded hole

Lightening Hole:

Not included

Protruding Hub Characteristic:

Plain

Securing Location:

Aa end

Belt/chain/film Size For Which Designed:

Roller chain

Roller Chain Pitch Type For Which Designed:

Single pitch

Teeth Row Quantity:

1

Teeth Quantity Per Row:

24

Asa Standard Chain Number:

60

Hardness Rating Test Method:

Not rated

Bore Bearing:

Not included

Hub External Keyway:

Not included

Tooth Pitch:

0.750 inches

Hub End Outside Diameter And Location:

2.937 inches aa end and 3.063 inches aa end

Distance From Outside Flange/rim To Hub End And Location:

0.989 inches aa end and 1.103 inches aa end

Material:

Steel, qq-s-633, fs1020-canceled

Material:

Steel comp 1020

Material Specification:

Qq-s-633, fs1020-canceled federal specification single material response

Surface Treatment:

Phosphate

Style Designator:

Plain

Surface Treatment:

Phosphate coated

Fsc Application Data:

Winch, tank recovery vehicle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T353-c