

View Online at <https://aerobasegroup.com/nsn/3020-00-288-3414>

**Counterbore Diameter:**

Between 5.500 inches and 6.375 inches

**Counterbore Depth:**

Between 0.219 inches and 0.875 inches

**Groove Depth:**

0.687 inches

**Groove Width:**

0.675 inches

**Outside Diameter:**

7.313 inches

**Overall Length:**

2.375 inches

**Keyway Width:**

0.188 inches

**Thread Size:**

5/16-18

**Bore Diameter:**

0.750 inches

**Bore Length:**

2.375 inches

**Distance From Center Of Bore To Bottom Of Keyway:**

0.469 inches

**Key Spacing In Deg:**

90.0

**V Groove Angle In Deg:**

34.0

**Pitch Diameter:**

7.000 inches

**Securing Hole Quantity:**

2

**Material And Location:**

Iron, cast, qq-i-652, class 20

**Face Width:**

1.750 inches

**Design Form:**

Spoked

**Bore Type:**

Straight

**Bearings:**

Not included

**Groove Quantity:**

2

**Counterbore Feature:**

Included

**Counterbore Location:**

Bb end

**Hole Location:**

One hole located on top of key 3/8 in. From end of hub, one hole 90 degrees from keyway 3/8 in. From end of hub

**Keying Facility:**

Included

**Keying Facility Type:**

Keyway

**Securing Method:**

Threaded hole

**Split Hub Feature:**

Not included

**Web/spoke Relationship To Face Centerline:**

Offset

**Lightening Hole:**

Not included

**Integral Cooling Vane:**

Not included

**Groove Shape:**

V

**Bore Feature:**

Included

**Protruding Hub Characteristic:**

Stepped

**Securing Location:**

Aa end

**First Step Face Largest Diameter And Location:**

2.688 inches aa end

**First Step Length And Location:**

0.750 inches aa end

**Hub End Outside Diameter And Location:**

2.500 inches aa end

**Distance From Outside Flange/rim To Hub End And Location:**

0.625 inches aa end

**Quantity:**

2

**Surface Treatment:**

Paint

**Style Designator:**

Webbed or spoked

**Surface Treatment:**

Painted

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T353-a