

View Online at <https://aerobasegroup.com/nsn/3020-00-288-3414>

Counterbore Diameter:

Between 5.500 inches and 6.375 inches

Counterbore Depth:

Between 0.219 inches and 0.875 inches

Groove Depth:

0.687 inches

Groove Width:

0.675 inches

Outside Diameter:

7.313 inches

Overall Length:

2.375 inches

Keyway Width:

0.188 inches

Thread Size:

5/16-18

Bore Diameter:

0.750 inches

Bore Length:

2.375 inches

Distance From Center Of Bore To Bottom Of Keyway:

0.469 inches

Key Spacing In Deg:

90.0

V Groove Angle In Deg:

34.0

Pitch Diameter:

7.000 inches

Securing Hole Quantity:

2

Material And Location:

Iron, cast, qq-i-652, class 20

Face Width:

1.750 inches

Design Form:

Spoked

Bore Type:

Straight

Bearings:

Not included

Groove Quantity:

2

Counterbore Feature:

Included

Counterbore Location:

Bb end

Hole Location:

One hole located on top of key 3/8 in. From end of hub, one hole 90 degrees from keyway 3/8 in. From end of hub

Keying Facility:

Included

Keying Facility Type:

Keyway

Securing Method:

Threaded hole

Split Hub Feature:

Not included

Web/spoke Relationship To Face Centerline:

Offset

Lightening Hole:

Not included

Integral Cooling Vane:

Not included

Groove Shape:

V

Bore Feature:

Included

Protruding Hub Characteristic:

Stepped

Securing Location:

Aa end

First Step Face Largest Diameter And Location:

2.688 inches aa end

First Step Length And Location:

0.750 inches aa end

Hub End Outside Diameter And Location:

2.500 inches aa end

Distance From Outside Flange/rim To Hub End And Location:

0.625 inches aa end

Quantity:

2

Surface Treatment:

Paint

Style Designator:

Webbed or spoked

Surface Treatment:

Painted

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T353-a