## NSN 3020-00-288-5825

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-288-5825

## Body Style:

Plain, with lightening holes

## **Attachment Method:**

Mounting hole

## Pitch Diameter:

2.3750 inches

## **Teeth Quantity:**

114

#### Bore Style:

W/counterbore both ends

### **Backlash Designation:**

Grade c

#### Mounting Hole Type And Quantity:

2 plain axially through body, first end

### Outside Diameter:

#### 2.416 inches

Nominallength:

0.635 inches

#### Tooth Form:

Standard

#### Pressure Angle:

20.0000 degrees

## Distance Between Body Face And Protruding Hub End:

0.528 inches first end

## Face Width:

0.109 inches

#### Bore Diameter:

0.250 inches both ends

#### **Counterbore Depth:**

0.215 inches both ends

#### **Counterbore Diameter:**

0.830 inches both ends

#### Hub Style Designator:

1 groove first end

#### End Diameter:

1.562 inches first end

## First Groove Width:

0.419 inches first end

#### First Groove Diameter:

1.062 inches first end

## **Distance From End To First Groove:**

0.107 inches first end

# NSN 3020-00-288-5825

Spur Gear - Page 2 of 2



Mounting Hole Diameter:

0.187 inches axially through body, first end

## **Bolt Hole Circle Diameter:**

1.208 inches axially through body, first end

Material:

Copper alloy 360

## Material Specification:

Qq-b-611, comp b, 1/2h federal specification single material response

#### Surface Treatment:

Chromate

Style Designator:

Protruding hub

Shelf Life:

N/a

#### Unit Of Measure:

--

## Demilitarization:

No

#### Fiig:

A27300