NSN 3020-00-288-5858

Spur Gear - Page 1 of 2





Body Style: Plain, solid **Attachment Method:** Mounting hole **Pitch Diameter:** Between 4.6847 inches and 4.6861 inches **Teeth Quantity:** 225 Bore Style: W/counterbore both ends Mounting Hole Thread Series Designator: Unc axially through body, first end Mounting Hole Thready Qty Per Inch (tpi): 32 axially through body, first end Mounting Hole Thread Size: 0.138 inches axially through body, first end Mounting Hole Type And Quantity: 4 threaded axially through body, first end **Outside Diameter:** 4.726 inches Nominallength: 0.690 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.590 inches first end Face Width: 0.100 inches **Bore Diameter:** 2.190 inches both ends **Counterbore Depth:** 0.220 inches second end **Counterbore Diameter:** 3.560 inches second end **Bolt Hole Circle Diameter:** 3.500 inches axially through body, first end Material: Copper alloy Style Designator: Protruding hub

NSN 3020-00-288-5858

Spur Gear - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A27300

