NSN 3020-00-289-7763

Spur Gear - Page 1 of 2

Body Style:



View Online at https://aerobasegroup.com/nsn/3020-00-289-7763

| Plain, solid |
|--|
| Attachment Method: |
| Mounting hole |
| Pitch Diameter: |
| 3.2000 inches |
| Teeth Quantity: |
| 64 |
| Bore Style: |
| Plain both ends |
| Backlash Designation: |
| Grade a |
| Hardness Rating: |
| 293.0 brinell standard and 341.0 brinell standard teeth |
| Mounting Hole Type And Quantity: |
| 1 plain transversely through hub, first end |
| Outside Diameter: |
| 3.300 inches |
| Tooth Form: |
| Standard |
| Pressure Angle: |
| 14.5000 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 0.500 inches first end |
| Face Width: |
| 0.375 inches |
| Bore Diameter: |
| 0.5937 inches first end |
| Keyway Width: |
| 0.125 inches both ends |
| Distance From Bore Center To Keyway Bottom: |
| 0.3255 inches first end |
| Hub Style Designator: |
| Plain first end |
| |
| Hub Diameter: |
| |
| Hub Diameter: |
| Hub Diameter: 1.000 inches first end |
| Hub Diameter: 1.000 inches first end Mounting Hole Diameter: |
| Hub Diameter: 1.000 inches first end Mounting Hole Diameter: 0.128 inches transversely through hub, first end |
| Hub Diameter: 1.000 inches first end Mounting Hole Diameter: 0.128 inches transversely through hub, first end Material: |
| Hub Diameter: 1.000 inches first end Mounting Hole Diameter: 0.128 inches transversely through hub, first end Material: Steel comp 1141 |

NSN 3020-00-289-7763

Spur Gear - Page 2 of 2



| Ctv/la | n Da | eian | ator: |
|--------|------|-------|-------|
| OLYN | - 00 | əiyii | atoi. |

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300