NSN 3020-00-289-7763

Spur Gear - Page 1 of 2

Body Style:



View Online at https://aerobasegroup.com/nsn/3020-00-289-7763

Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
3.2000 inches
Teeth Quantity:
64
Bore Style:
Plain both ends
Backlash Designation:
Grade a
Hardness Rating:
293.0 brinell standard and 341.0 brinell standard teeth
Mounting Hole Type And Quantity:
1 plain transversely through hub, first end
Outside Diameter:
3.300 inches
Tooth Form:
Standard
Pressure Angle:
14.5000 degrees
Distance Between Body Face And Protruding Hub End:
0.500 inches first end
Face Width:
0.375 inches
Bore Diameter:
0.5937 inches first end
Keyway Width:
0.125 inches both ends
Distance From Bore Center To Keyway Bottom:
0.3255 inches first end
Hub Style Designator:
Plain first end
Hub Diameter:
Hub Diameter:
Hub Diameter: 1.000 inches first end
Hub Diameter: 1.000 inches first end Mounting Hole Diameter:
Hub Diameter: 1.000 inches first end Mounting Hole Diameter: 0.128 inches transversely through hub, first end
Hub Diameter: 1.000 inches first end Mounting Hole Diameter: 0.128 inches transversely through hub, first end Material:
Hub Diameter: 1.000 inches first end Mounting Hole Diameter: 0.128 inches transversely through hub, first end Material: Steel comp 1141

NSN 3020-00-289-7763

Spur Gear - Page 2 of 2



Ctv/la	n Da	eian	ator:
OLYN	- 00	əiyii	atoi.

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300