## NSN 3020-00-289-7796



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-289-7796 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 0.7500 inches **Teeth Quantity:** 36 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 32 transversely through hub, first end **Mounting Hole Thread Size:** 0.138 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 1 plain transversely through hub, first end and 1 threaded transversely through hub, first end **Outside Diameter:** 0.791 inches Nominallength: 0.375 inches **Tooth Form:** Standard **Pressure Angle:** 14.5000 degrees **Distance Between Body Face And Protruding Hub End:** 0.250 inches first end **Face Width:** 0.125 inches **Bore Diameter:** 0.249 inches both ends **Hub Style Designator:** Pinned first end **Hub Diameter:** 0.500 inches first end **Mounting Hole Diameter:** 0.078 inches transversely through hub, first end Material:

Oxide

Copper alloy

**Surface Treatment:** 

## NSN 3020-00-289-7796

Spur Gear - Page 2 of 2



Protruding hub

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A27300