

View Online at <https://aerobasegroup.com/nsn/3020-00-289-7912>

**Outside Diameter:**

12.500 inches

**Overall Length:**

3.625 inches

**Keyway Width:**

0.3735 inches

**Bore Diameter:**

1.6245 inches

**Bore Length:**

3.625 inches

**Distance From Center Of Bore To Bottom Of Keyway:**

0.99975 inches

**Pitch Diameter:**

11.302 inches

**Face Width:**

1.250 inches

**Design Form:**

Plain

**Bore Type:**

Straight

**Counterbore Feature:**

Not included

**Keying Facility:**

Included

**Keying Facility Type:**

Keyway

**Lightening Hole:**

Not included

**Protruding Hub Characteristic:**

Stepped

**Groove/step Location:**

Aa end

**Belt/chain/film Size For Which Designed:**

Roller chain

**Roller Chain Pitch Type For Which Designed:**

Single pitch

**Teeth Row Quantity:**

1

**Teeth Quantity Per Row:**

14

**Hardness Rating Test Method:**

Not rated

**Bore Bearing:**

Not included

**Hub External Keyway:**

Not included

**Tooth Pitch:**

2.500 inches

**Hub End Outside Diameter And Location:**

3.000 inches both ends

**Distance From Outside Flange/rim To Hub End And Location:**

0.906 inches bb end

**First Step Face Largest Diameter And Location:**

3.000 inches aa end

**First Step Length And Location:**

0.875 inches aa end

**Hub End Outside Diameter And Location:**

2.500 inches aa end

**Distance From Outside Flange/rim To Hub End And Location:**

1.468 inches aa end

**Material:**

Steel, mil-s-890

**Material:**

Steel

**Material Specification:**

Mil-s-890 military specification single material response

**Quantity:**

1

**Style Designator:**

Plain

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T353-c

**Mil-std (military Standard):**

Mil-s-890 spec.