

View Online at <https://aerobasegroup.com/nsn/3020-00-289-7928>

Outside Diameter:

9.796 inches

Overall Length:

1.875 inches

Keyway Width:

Between 0.499 inches and 0.500 inches

Bore Length:

1.875 inches

Distance From Center Of Bore To Bottom Of Keyway:

1.333 inches

Pitch Diameter:

9.249 inches

Taper Bore Major Diameter:

Between 2.166 inches and 2.171 inches

Face Width:

Between 1.690 inches and 1.718 inches

Design Form:

Webbed

Bore Type:

Straight

Counterbore Feature:

Not included

Keying Facility:

Included

Keying Facility Type:

Keyway

Lightening Hole:

Not included

Protruding Hub Characteristic:

Plain

Belt/chain/film Size For Which Designed:

Roller chain

Roller Chain Pitch Type For Which Designed:

Single pitch

Teeth Row Quantity:

2

Center To Center Distance Between Teeth Rows:

1.153 inches

Teeth Quantity Per Row:

29

Asa Standard Chain Number:

80-2

Hardness Rating Test Method:

Not rated

Bore Bearing:

Not included

Hub External Keyway:

Not included

Tooth Pitch:

1.000 inches

Hub End Outside Diameter And Location:

3.625 inches both ends

Distance From Outside Flange/rim To Hub End And Location:

0.143 inches aa end and 0.153 inches aa end and 0.023 inches bb end

Special Features:

2 holes 0.750 in. Diameter 180 degrees apart on 5.500 in. Diameter bolt circle, one hole located on top of keyway

Material:

Steel, mil-s-16788

Material:

Steel comp 1010 or steel comp 1020 or steel comp 1030 or steel comp 1040 or steel comp 1050 or steel comp 1060 or steel comp 1080 or steel comp 1095

Material Specification:

Mil-s-16788 military specification single material response

Quantity:

1

Style Designator:

Webbed or spoked

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T353-c

Mil-std (military Standard):

Mil-s-16788 spec.