NSN 3020-00-289-7929

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-289-7929

| Outside Diameter: |
|---|
| 11.718 inches |
| Overall Length: |
| 1.875 inches |
| Keyway Width: |
| Between 0.499 inches and 0.500 inches |
| Bore Diameter: |
| Between 2.1660 inches and 2.1665 inches |
| Bore Length: |
| 1.875 inches |
| Distance From Center Of Bore To Bottom Of Keyway: |
| 1.333 inches |
| Pitch Diameter: |
| 11.156 inches |
| Face Width: |
| Between 1.770 inches and 1.798 inches |
| Design Form: |
| Webbed |
| Bore Type: |
| Straight |
| Counterbore Feature: |
| Not included |
| Keying Facility: |
| Included |
| Keying Facility Type: |
| Keyway |
| Lightening Hole: |
| Not included |
| Belt/chain/film Size For Which Designed: |
| Roller chain |
| Roller Chain Pitch Type For Which Designed: |
| Single pitch |
| Teeth Row Quantity: |
| 2 |
| Center To Center Distance Between Teeth Rows: |
| 1.153 inches |
| Teeth Quantity Per Row: |
| 35 |
| Asa Standard Chain Number: |
| 80-2 |
| Hardness Rating Test Method: |
| Not rated |

Not rated

NSN 3020-00-289-7929 Sprocket Wheel - Page 2 of 2



| Bore Bearing: |
|--|
| Not included |
| Hub External Keyway: |
| Not included |
| Tooth Pitch: |
| 1.000 inches |
| Hub End Outside Diameter And Location: |
| 3.625 inches both ends |
| Distance From Outside Flange/rim To Hub End And Location: |
| 0.143 inches aa end and 0.153 inches aa end and 0.023 inches bb end |
| Special Features: |
| 2 holes 0.750 in. Diameter 180 degrees apart on 7.375 in. Diameter bolt circle, one hole located on top of keyway |
| Material: |
| Steel, mil-s-16788 |
| Material: |
| Steel comp 1010 or steel comp 1020 or steel comp 1030 or steel comp 1040 or steel comp 1050 or steel comp 1060 or steel comp 1080 or |
| steel comp 1095 |
| Material Specification: |
| Mil-s-16788 military specification single material response |
| Quantity: |
| 1 |
| Style Designator: |
| Webbed or spoked |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| T353-c |
| Mil-std (military Standard): |
| Mil-s-16788 spec. |
| |
| |