## NSN 3020-00-289-7929

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-289-7929

Outside Diameter:
11.718 inches
Overall Length:
1.875 inches
Keyway Width:
Between 0.499 inches and 0.500 inches
Bore Diameter:
Between 2.1660 inches and 2.1665 inches
Bore Length:
1.875 inches
Distance From Center Of Bore To Bottom Of Keyway:
1.333 inches
Pitch Diameter:
11.156 inches
Face Width:
Between 1.770 inches and 1.798 inches
Design Form:
Webbed
Bore Type:
Straight
Counterbore Feature:
Not included
Keying Facility:
Included
Keying Facility Type:
Keyway
Lightening Hole:
Not included
Belt/chain/film Size For Which Designed:
Roller chain
Roller Chain Pitch Type For Which Designed:
Single pitch
Teeth Row Quantity:
2
Center To Center Distance Between Teeth Rows:
1.153 inches
Teeth Quantity Per Row:
35
Asa Standard Chain Number:
80-2
Hardness Rating Test Method:
Not rated

Not rated

## **NSN 3020-00-289-7929** Sprocket Wheel - Page 2 of 2



Bore Bearing:
Not included
Hub External Keyway:
Not included
Tooth Pitch:
1.000 inches
Hub End Outside Diameter And Location:
3.625 inches both ends
Distance From Outside Flange/rim To Hub End And Location:
0.143 inches aa end and 0.153 inches aa end and 0.023 inches bb end
Special Features:
2 holes 0.750 in. Diameter 180 degrees apart on 7.375 in. Diameter bolt circle, one hole located on top of keyway
Material:
Steel, mil-s-16788
Material:
Steel comp 1010 or steel comp 1020 or steel comp 1030 or steel comp 1040 or steel comp 1050 or steel comp 1060 or steel comp 1080 or
steel comp 1095
Material Specification:
Mil-s-16788 military specification single material response
Quantity:
1
Style Designator:
Webbed or spoked
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
T353-c
Mil-std (military Standard):
Mil-s-16788 spec.