

View Online at <https://aerobasegroup.com/nsn/3020-00-291-1861>

**Outside Diameter:**

2.093 inches

**Overall Length:**

Between 0.870 inches and 0.875 inches

**Bore Diameter:**

Between 0.4370 inches and 0.4375 inches

**Bore Length:**

Between 0.870 inches and 0.875 inches

**Pitch Diameter:**

1.827 inches

**Face Width:**

0.343 inches

**Design Form:**

Plain

**Bore Type:**

Straight

**Metallic Hardness Rating And Location:**

363.0 brinell standard body and 363.0 brinell standard hub

**Counterbore Feature:**

Not included

**Lubrication Mode:**

Visible means

**Keying Facility:**

Not included

**Lightening Hole:**

Not included

**Protruding Hub Characteristic:**

Stepped

**Groove/step Location:**

Both ends

**Belt/chain/film Size For Which Designed:**

Ladder chain

**Teeth Row Quantity:**

1

**Teeth Quantity Per Row:**

9

**Asa Standard Chain Number:**

50-1

**Hardness Rating Test Method:**

Brinell

**Teeth Hardness Rating:**

363.0 brinell standard

**Bore Bearing:**

Included

**Hub External Keyway:**

Not included

**Tooth Pitch:**

0.625 inches

**First Step Face Largest Diameter And Location:**

1.063 inches both ends

**First Step Length And Location:**

0.060 inches both ends and 0.063 inches both ends

**Second Step Length And Location:**

0.203 inches both ends and 0.204 inches both ends

**Hub End Outside Diameter And Location:**

0.8125 inches both ends and 0.8130 inches both ends

**Distance From Outside Flange/rim To Hub End And Location:**

0.263 inches both ends and 0.267 inches both ends

**Criticality Code Justification:**

Abxv and clyr

**Material:**

Cres, ams 5629

**Material:**

Cres, ams 5629

**Style Designator:**

Plain

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

T353-c