

View Online at <https://aerobasegroup.com/nsn/3020-00-291-1861>

Outside Diameter:

2.093 inches

Overall Length:

Between 0.870 inches and 0.875 inches

Bore Diameter:

Between 0.4370 inches and 0.4375 inches

Bore Length:

Between 0.870 inches and 0.875 inches

Pitch Diameter:

1.827 inches

Face Width:

0.343 inches

Design Form:

Plain

Bore Type:

Straight

Metallic Hardness Rating And Location:

363.0 brinell standard body and 363.0 brinell standard hub

Counterbore Feature:

Not included

Lubrication Mode:

Visible means

Keying Facility:

Not included

Lightening Hole:

Not included

Protruding Hub Characteristic:

Stepped

Groove/step Location:

Both ends

Belt/chain/film Size For Which Designed:

Ladder chain

Teeth Row Quantity:

1

Teeth Quantity Per Row:

9

Asa Standard Chain Number:

50-1

Hardness Rating Test Method:

Brinell

Teeth Hardness Rating:

363.0 brinell standard

Bore Bearing:

Included

Hub External Keyway:

Not included

Tooth Pitch:

0.625 inches

First Step Face Largest Diameter And Location:

1.063 inches both ends

First Step Length And Location:

0.060 inches both ends and 0.063 inches both ends

Second Step Length And Location:

0.203 inches both ends and 0.204 inches both ends

Hub End Outside Diameter And Location:

0.8125 inches both ends and 0.8130 inches both ends

Distance From Outside Flange/rim To Hub End And Location:

0.263 inches both ends and 0.267 inches both ends

Criticality Code Justification:

Abxv and clyr

Material:

Cres, ams 5629

Material:

Cres, ams 5629

Style Designator:

Plain

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T353-c