NSN 3020-00-293-4024

Helical Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-293-4024

Body Style:					
Webbed, solid					
Attachment Method:					
Mounting hole					
Pitch Diameter:					
8.6250 inches					
Teeth Quantity:					
69					
Bore Style:					
Plain both ends					
Mounting Hole Thread Series Designator:					
Unf axially through body, second end					
Mounting Hole Thready Qty Per Inch (tpi):					
24 axially through body, second end					
Hardness Rating:					
10.0 rockwell c and 20.0 rockwell c					
Mounting Hole Thread Size:					
0.375 inches axially through body, second end					
Mounting Hole Type And Quantity:					
4 plain axially through body, first end					
Nominallength:					
2.062 inches					
Teeth Type:					
Single helix					
Tooth Form:					
Standard					
Tooth Direction:					
Left					
Pressure Angle:					
14.5000 degrees					
Helix Angle:					
25.81635 degrees					
Bore Diameter:					
4.375 inches both ends					
Hub Style Designator:					
Plain first end					
Hub Diameter:					
6.750 inches first end					
Mounting Hole Diameter:					
0.500 inches axially through body, first end					
Bolt Hole Circle Diameter:					

5.250 inches axially through body, second end

NSN 3020-00-293-4024

Helical Gear - Page 2 of 2



Special Features:

Outside diameter 8.873min. 8.875max. In.; bore provision included; bore length 0.438 in.; face width 1.745min. 1.755max. In.; distance from first end hub end to face of gear 0.3075min. 0.3175max. In.; depth from second end face of teeth to face of bore 0.3075min. 0.3175max. In.; web location offset from gear teeth centerline; style webbed, protruding hub/recessed face; circular pitch 0.3927 in.

	te		

Steel

Material Specification:

Mil-s-890, class b military specification single material response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-s-890 spec.