# NSN 3020-00-294-7662

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-294-7662

Body Style:

Plain, solid

**Attachment Method:** 

Mounting hole

**Pitch Diameter:** 

4.5000 inches

**Teeth Quantity:** 

27

Bore Style:

W/ keyway both ends

Mounting Hole Thread Series Designator:

Unf axially through body, first end

Mounting Hole Thready Qty Per Inch (tpi):

36 axially through body, first end

#### Hardness Rating:

96.0 rockwell c and 102.0 rockwell c

### Mounting Hole Thread Size:

0.164 inches transversely through hub, first end

# Mounting Hole Type And Quantity:

3 threaded axially through body, first end

# **Outside Diameter:**

4.875 inches

Tooth Form:

Standard

#### **Pressure Angle:**

14.5000 degrees

## Distance Between Body Face And Protruding Hub End:

0.250 inches first end

### Face Width:

1.000 inches

#### Bore Diameter:

2.502 inches both ends

#### Keyway Width:

0.250 inches both ends

## Distance From Bore Center To Keyway Bottom:

1.376 inches both ends

## Hub Style Designator:

Plain first end

Hub Diameter:

3.250 inches first end

#### **Bolt Hole Circle Diameter:**

2.875 inches axially through body, first end

# NSN 3020-00-294-7662

Spur Gear - Page 2 of 2



# **Special Features:**

3.375 in. Diameter by 0.125 in. Deep recess cut in face of gear

Material:

Aluminum

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300