NSN 3020-00-303-5226

Spur Gear - Page 1 of 2

Body Style: Err-090

Material Specification:

Og a 762 place 416 foderal appoification single material response



View Online at https://aerobasegroup.com/nsn/3020-00-303-5226

| Attachment Method: |
|---|
| Mounting hole |
| Pitch Diameter: |
| 0.5833 inches |
| Teeth Quantity: |
| 28 |
| Bore Style: |
| Plain first end |
| Mounting Hole Thread Series Designator: |
| Unc axially through hub, first end |
| Mounting Hole Thready Qty Per Inch (tpi): |
| 32 axially through hub, first end |
| Hardness Rating: |
| 25.0 rockwell c |
| Mounting Hole Thread Size: |
| 0.138 inches axially through hub, first end |
| Mounting Hole Type And Quantity: |
| 1 threaded axially through hub, first end |
| Tooth Form: |
| Standard |
| Pressure Angle: |
| 14.5000 degrees |
| Face Width: |
| 0.094 inches |
| Hub Style Designator: |
| 1 step first end |
| End Length: |
| 0.208 inches first end |
| End Diameter: |
| 0.250 inches first end |
| First Step Length: |
| 0.010 inches first end |
| First Step Diameter: |
| 0.4375 inches first end |
| Special Features: |
| Zone 0.035 in. Diameter hole through gear concentric w/ centerline of teeth 0.179 in from centerline of bore; bore provision included; bore |
| diameter 0.1719min 0.1722max in.; bore length 0.281min 0.282max in.; length 0.312min 0.313max in.; outside diameter 0.6271min |
| 0.6301max in.; distance from first end hub end to face of gear 0.218min 0.219 maximum in.; depth from second end face of teeth to face of |
| bore 0.03min 0.032max in.; web location on gear teeth centerline; circular pitch 0.06545 in. |
| Material: |
| Steel |

NSN 3020-00-303-5226 Spur Gear - Page 2 of 2



| Surrace Treatment: |
|--------------------------------------|
| Passivate |
| Style Designator: |
| One protruding hub, one recessed hub |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A27300