NSN 3020-00-303-5226

Spur Gear - Page 1 of 2

Body Style: Err-090

Material Specification:

Og a 762 place 416 foderal appoification single material response



View Online at https://aerobasegroup.com/nsn/3020-00-303-5226

Attachment Method:
Mounting hole
Pitch Diameter:
0.5833 inches
Teeth Quantity:
28
Bore Style:
Plain first end
Mounting Hole Thread Series Designator:
Unc axially through hub, first end
Mounting Hole Thready Qty Per Inch (tpi):
32 axially through hub, first end
Hardness Rating:
25.0 rockwell c
Mounting Hole Thread Size:
0.138 inches axially through hub, first end
Mounting Hole Type And Quantity:
1 threaded axially through hub, first end
Tooth Form:
Standard
Pressure Angle:
14.5000 degrees
Face Width:
0.094 inches
Hub Style Designator:
1 step first end
End Length:
0.208 inches first end
End Diameter:
0.250 inches first end
First Step Length:
0.010 inches first end
First Step Diameter:
0.4375 inches first end
Special Features:
Zone 0.035 in. Diameter hole through gear concentric w/ centerline of teeth 0.179 in from centerline of bore; bore provision included; bore
diameter 0.1719min 0.1722max in.; bore length 0.281min 0.282max in.; length 0.312min 0.313max in.; outside diameter 0.6271min
0.6301max in.; distance from first end hub end to face of gear 0.218min 0.219 maximum in.; depth from second end face of teeth to face of
bore 0.03min 0.032max in.; web location on gear teeth centerline; circular pitch 0.06545 in.
Material:
Steel

NSN 3020-00-303-5226 Spur Gear - Page 2 of 2



Surrace Treatment:
Passivate
Style Designator:
One protruding hub, one recessed hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A27300