NSN 3020-00-305-0313

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-305-0313

Body Style:
Plain, solid
Spline Quantity:
15 both ends
Pitch Diameter:
2.0000 inches
Teeth Quantity:
24
Bore Style:
Involute spline both ends
Spline Pitch Diameter:
0.4688 inches both ends
Hardness Rating:
60.0 rockwell c teeth
Outside Diameter:
2.1575 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
1.1600 inches first end
Face Width:
0.770 inches
Bore Diameter:
0.4690 inches both ends
Hub Style Designator:
1 step both ends
End Length:
0.6400 inches second end
Precision Classification:
Quality number 9
End Diameter:
1.1807 inches second end
First Step Length:
0.6130 inches first end
First Step Diameter:
1.3600 inches second end
Special Features:
Counterbore 1st end, 0.875 in. Dia, 2.060 in. Dp
Material:
Steel comp 9310h

NSN 3020-00-305-0313

Spur Gear - Page 2 of 2

A27300

Mil-std (military Standard):

Mil-p-16232 spec.



Material Specification:
Qq-s-624 federal specification single material response
Surface Treatment:
Phosphate manganese
Surface Treatment Specification:
Mil-p-16232, type m, class 1 military specification single treatment response
Style Designator:
Protruding hubs
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: