NSN 3020-00-305-1961

Gear Cluster - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3020-00-305-1961

Attachment Method:
Mounting hole
Bore Style:
Plain both ends
Design Type:
Spur second gear
Construction:
Solid
Thread Size:
0.112 inches both ends
Outside Diameter:
3.040 inches first gear
Nominallength:
0.687 inches
Hub Length:
0.437 inches between first and second gear
Bore Diameter:
0.188 inches both ends
Hub Style Designator:
Plain first end
Hub Diameter:
nub biameter.
0.375 inches between first and second gear
0.375 inches between first and second gear
0.375 inches between first and second gear Precision Classification:
0.375 inches between first and second gear Precision Classification: Quality number 10 all gears or quality number 11 all gears
0.375 inches between first and second gear Precision Classification: Quality number 10 all gears or quality number 11 all gears Special Features:
0.375 inches between first and second gear Precision Classification: Quality number 10 all gears or quality number 11 all gears Special Features: Attaching holes spaced 90 degrees apart
0.375 inches between first and second gear Precision Classification: Quality number 10 all gears or quality number 11 all gears Special Features: Attaching holes spaced 90 degrees apart Material:
0.375 inches between first and second gear Precision Classification: Quality number 10 all gears or quality number 11 all gears Special Features: Attaching holes spaced 90 degrees apart Material: Steel comp 416
0.375 inches between first and second gear Precision Classification: Quality number 10 all gears or quality number 11 all gears Special Features: Attaching holes spaced 90 degrees apart Material: Steel comp 416 Material Specification:
0.375 inches between first and second gear Precision Classification: Quality number 10 all gears or quality number 11 all gears Special Features: Attaching holes spaced 90 degrees apart Material: Steel comp 416 Material Specification: Aisi 416/sae 51416 assn standard single material response
0.375 inches between first and second gear Precision Classification: Quality number 10 all gears or quality number 11 all gears Special Features: Attaching holes spaced 90 degrees apart Material: Steel comp 416 Material Specification: Aisi 416/sae 51416 assn standard single material response Surface Treatment:
0.375 inches between first and second gear Precision Classification: Quality number 10 all gears or quality number 11 all gears Special Features: Attaching holes spaced 90 degrees apart Material: Steel comp 416 Material Specification: Aisi 416/sae 51416 assn standard single material response Surface Treatment: Passivate
0.375 inches between first and second gear Precision Classification: Quality number 10 all gears or quality number 11 all gears Special Features: Attaching holes spaced 90 degrees apart Material: Steel comp 416 Material Specification: Aisi 416/sae 51416 assn standard single material response Surface Treatment: Passivate Shelf Life:
0.375 inches between first and second gear Precision Classification: Quality number 10 all gears or quality number 11 all gears Special Features: Attaching holes spaced 90 degrees apart Material: Steel comp 416 Material Specification: Aisi 416/sae 51416 assn standard single material response Surface Treatment: Passivate Shelf Life: N/a
0.375 inches between first and second gear Precision Classification: Quality number 10 all gears or quality number 11 all gears Special Features: Attaching holes spaced 90 degrees apart Material: Steel comp 416 Material Specification: Aisi 416/sae 51416 assn standard single material response Surface Treatment: Passivate Shelf Life: N/a
0.375 inches between first and second gear Precision Classification: Quality number 10 all gears or quality number 11 all gears Special Features: Attaching holes spaced 90 degrees apart Material: Steel comp 416 Material Specification: Aisi 416/sae 51416 assn standard single material response Surface Treatment: Passivate Shelf Life: N/a Unit Of Measure:
0.375 inches between first and second gear Precision Classification: Quality number 10 all gears or quality number 11 all gears Special Features: Attaching holes spaced 90 degrees apart Material: Steel comp 416 Material Specification: Aisi 416/sae 51416 assn standard single material response Surface Treatment: Passivate Shelf Life: N/a Unit Of Measure: Demilitarization: