NSN 3020-00-306-5865

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-306-5865

Body Style: Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 1.7720 inches **Teeth Quantity:** 22 **Bore Style:** W/counterbore both ends **Hardness Rating:** 32.0 rockwell c and 40.0 rockwell c **Mounting Hole Type And Quantity:** 3 plain transversely through hub, first end **Outside Diameter:** 1.975 inches Nominallength: 8.2200 inches **Tooth Form:** Standard Pressure Angle: 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 4.730 inches first end Face Width: 0.360 inches **Bore Diameter:** 0.270 inches both ends **Counterbore Depth:** 0.590 inches both ends **Counterbore Diameter:** 0.500 inches both ends **Hub Style Designator:** Plain second end **Hub Diameter:** 0.934 inches second end **End Length:** 1.200 inches first end

End Diameter:

0.952 inches first end

First Step Length:

1.110 inches first end

NSN 3020-00-306-5865 Spur Gear - Page 2 of 2



First Step Diameter:
1.095 inches first end
Second Step Length:
2.420 inches first end
Second Step Diameter:
1.101 inches first end
Mounting Hole Diameter:
0.125 inches transversely through hub, first end
Material:
Steel comp e9310
Material Specification:
Ams 6260 assn standard single material response
Style Designator:
Protruding hubs
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300