NSN 3020-00-314-0563

Sprocket Wheel - Page 1 of 2

Outside Diameter:



View Online at https://aerobasegroup.com/nsn/3020-00-314-0563

Between 11.141 inches and 11.156 inches
Overall Length:
2.875 inches
Key Width:
Between 0.500 inches and 0.502 inches
Thread Size:
3/8-24 thd size
Bore Diameter:
Between 2.000 inches and 2.001 inches
Bore Length:
2.875 inches
Distance From Center Of Bore To Bottom Of Keyway:
Between 1.228 inches and 1.238 inches
Pitch Diameter:
11.156 inches
Securing Hole Quantity:
1
Face Width:
Between 1.469 inches and 1.500 inches
Guide:
Not included
Design Form:
Webbed
Bore Type:
Straight
Counterbore Feature:
Not included
Hole Location:
Located on top of keyway
Keying Facility:
Included
Keying Facility Type:
Keyway
Securing Method:
Threaded hole
Lightening Hole:
Not included
Securing Location:
Aa end
Belt/chain/film Size For Which Designed:
Silent chain

NSN 3020-00-314-0563 Sprocket Wheel - Page 2 of 2



Teeth Row Quantity:
1
Teeth Quantity Per Row:
35
Hardness Rating Test Method:
Not rated
Bore Bearing:
Not included
Hub External Keyway:
Not included
Tooth Pitch:
1.000 inches
Hub End Outside Diameter And Location:
3.310 inches aa end and 3.314 inches aa end and 3.3125 inches bb end
Distance From Outside Flange/rim To Hub End And Location:
1.344 inches aa end and 1.375 inches aa end
Material:
Steel
Material:
Steel
Quantity:
1
Style Designator:
Webbed or spoked
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T353-c
No Fiig: