NSN 3020-00-316-2432

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-316-2432

Body Style:

Webbed, offset, solid

Spline Quantity:

12 both ends

Pitch Diameter:

5.6000 inches

Teeth Quantity:

56

Bore Style:

Involute spline both ends

Spline Pitch Diameter:

0.6000 inches both ends

Hardness Rating:

30.0 rockwell c and 33.0 rockwell c

Outside Diameter:

5.762 inches

Tooth Form:

Standard

Pressure Angle:

20.0000 degrees

Distance Between Body Face And Protruding Hub End:

2.256 inches first end

Face Width:

0.250 inches

Bore Diameter:

0.694 inches both ends

Hub Style Designator:

Plain second end

Hub Diameter:

1.220 inches second end

End Length:

2.156 inches first end

End Diameter:

0.8731 inches first end

First Step Length:

0.100 inches first end

First Step Diameter:

1.310 inches first end

Special Features:

Counterbore second end, depth 1.860 inches , 0.694

Material:

Steel

NSN 3020-00-316-2432

Spur Gear - Page 2 of 2



Material Specification:

Ams 6322 assn standard single material response

Style Designator:

Protruding hubs

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A27300