NSN 3020-00-316-7631

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-316-7631 **Body Style:** Plain, solid **Spline Quantity:** 15 both ends **Attachment Method:** Mounting hole Pitch Diameter: 4.1250 inches **Teeth Quantity:** 33 **Bore Style:** Involute spline both ends **Spline Pitch Diameter:** 1.5000 inches both ends Hardness Rating: 58.0 rockwell c and 62.0 rockwell c **Mounting Hole Type And Quantity:** 12 plain axially through flange **Outside Diameter:** 4.372 inches **Tooth Form:** Standard Flange Diameter: 7.250 inches Pilot Length: 0.880 inches **Pressure Angle:** 20.0000 degrees Flange Thickness: 0.380 inches **Face Width:** 0.500 inches **Bore Diameter:** 1.615 inches both ends **Distance Between Outer Body Face And Inner Flange Face:** 2.310 inches

Counterbore Depth: 0.690 inches first end

Counterbore Diameter:

4.1250 inches second end

Hub Diameter:

2.250 inches between body and flange

NSN 3020-00-316-7631 Spur Gear - Page 2 of 2



Pilot Diameter:	
2.832 inches	
Mounting Hole Diameter:	
0.595 inches axially through flange	
Bolt Hole Circle Diameter:	
6.000 inches axially through flange	
Special Features:	
Spline minor dia. 1.442 in. Nom	
Material:	
Steel comp 8620	
Material Specification:	
66, aisi/sae 8620 federal standard single material response	
Style Designator:	
Flanged end with pilot	
Shelf Life:	
N/a	
Unit Of Measure:	
.	
Demilitarization:	
No	
Fiig:	
A27300	