NSN 3020-00-317-6522

Spur Gear - Page 1 of 2

Webbed, offset, with lightening holes

Body Style:

Mounting hole

Pitch Diameter:
12.0000 inches

Teeth Quantity:

Attachment Method:



View Online at https://aerobasegroup.com/nsn/3020-00-317-6522

50
Bore Style:
Plain both ends
Backlash Designation:
Grade d
Hardness Rating:
58.0 rockwell c and 62.0 rockwell c
Mounting Hole Type And Quantity:
6 plain axially through hub, first end
Outside Diameter:
12.198 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Body Recess Depth:
0.340 inches first end
Face Width:
0.625 inches
Bore Diameter:
4.750 inches both ends
Hub Style Designator:
Plain first end
Hub Diameter:
6.750 inches first end
Precision Classification:
Quality number 13
Mounting Hole Diameter:
0.340 inches axially through hub, first end
Bolt Hole Circle Diameter:
5.750 inches axially through hub, first end
Material:
Steel comp 8617
Material Specification:
Fed standard 66 federal standard single material response

NSN 3020-00-317-6522

Spur Gear - Page 2 of 2



•	_		
Style	מווי	CIUI	12t∩r•
OLYIC	De	s ıgı	nator:

Flush hub

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300