## NSN 3020-00-317-6522

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-317-6522

#### **Body Style:**

Webbed, offset, with lightening holes

#### **Attachment Method:**

Mounting hole

## Pitch Diameter:

12.0000 inches

## **Teeth Quantity:**

96

Bore Style:

Plain both ends

## **Backlash Designation:**

Grade d

#### Hardness Rating:

58.0 rockwell c and 62.0 rockwell c

#### Mounting Hole Type And Quantity:

#### 6 plain axially through hub, first end

**Outside Diameter:** 

#### 12.198 inches

Tooth Form:

Standard

## Pressure Angle:

20.0000 degrees

#### Body Recess Depth:

0.340 inches first end

#### Face Width:

0.625 inches

#### Bore Diameter:

4.750 inches both ends

#### Hub Style Designator:

Plain first end

#### Hub Diameter:

6.750 inches first end

#### **Precision Classification:**

Quality number 13

#### Mounting Hole Diameter:

0.340 inches axially through hub, first end

## **Bolt Hole Circle Diameter:**

5.750 inches axially through hub, first end

#### Material:

Steel comp 8617

#### **Material Specification:**

Fed standard 66 federal standard single material response

# NSN 3020-00-317-6522

Spur Gear - Page 2 of 2

Style Designator:

Flush hub

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A27300

