## NSN 3020-00-320-2564

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-320-2564 **Body Style:** Webbed, offset, solid **Spline Quantity:** 34 both ends Pitch Diameter: 3.5000 inches **Teeth Quantity:** 35 **Bore Style:** Involute spline both ends **Spline Pitch Diameter:** 1.0625 inches both ends **Outside Diameter:** 3.698 inches Nominallength: 0.750 inches **Tooth Form:** Standard Pressure Angle: 25.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.119 inches both ends **Face Width:** 0.500 inches **Bore Diameter:** 1.078 inches both ends **Hub Style Designator:** Plain both ends **Hub Diameter:** 1.250 inches both ends Material: Steel comp e9310 **Material Specification:** Ams 6260 assn standard single material response **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13924, class 2 military specification single treatment response **Style Designator:** Protruding hubs Shelf Life:

N/a

## NSN 3020-00-320-2564

Spur Gear - Page 2 of 2



|  | ι | Jn | it | Of | Measure: |
|--|---|----|----|----|----------|
|--|---|----|----|----|----------|

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-c-13924 spec.