

View Online at <https://aerobasegroup.com/nsn/3020-00-321-6403>

Outside Diameter:

8.375 inches

Overall Length:

3.812 inches

Outside Diameter:

8.375 inches

Keyway Width:

Between 0.251 inches and 0.253 inches

Bore Length:

1.500 inches

Distance From Center Of Bore To Bottom Of Keyway:

0.633 inches

Flange Width:

0.125 inches

Drilled Hole Diameter:

0.250 inches

Pitch Diameter:

Between 5.437 inches and 5.446 inches

Flange Quantity:

1

Securing Hole Quantity:

1

Taper Bore Major Diameter:

1.001 inches

Taper Bore Minor Diameter:

0.814 inches

Material And Location:

Iron, qq-i-666, grade 2

Face Width:

0.689 inches

Design Form:

Webbed

Bore Type:

Tapered

Bearings:

Not included

Taper Major Diameter Location:

Aa end

Counterbore Feature:

Not included

Hole Location:

On pulley surface

Keying Facility:

Included

Keying Facility Type:

Keyway

Securing Method:

Drilled hole

Split Hub Feature:

Not included

Web/spoke Relationship To Face Centerline:

Not offset

Lightening Hole:

Not included

Integral Cooling Vane:

Not included

Crown Face:

Not included

Rim Type:

Solid

Flange Location:

Outside

Bore Feature:

Included

Protruding Hub Characteristic:

Plain

Securing Location:

Pulley surface

Hub End Outside Diameter And Location:

2.000 inches aa end and 1.625 inches bb end

Distance From Outside Flange/rim To Hub End And Location:

2.988 inches aa end and 2.187 inches bb end

Quantity:

1

Surface Treatment:

Phosphate and enamel

Style Designator:

Webbed or spoked

Surface Treatment:

Phosphate and enameled

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T353-a